



MODEL	LG50DT	LG60DT	LG70DT
Power type	Diesel	Diesel	Diesel
Rated capacity (Kg)	5000	6000	7000
J Load centre (mm)	600	600	600
h1 STD Max lifting height (mm)	3000	3000	3000
h3 Free lifting height (mm)	200	200	210
L5*W*T STD Fork size (mm)	1220*150*60	1220*150*60	1220*150*65
Mast tilt angle (deg)	6/12	6/12	6/12
L3 Front overhang (mm)	589	589	589
L4 Rear overhang (mm)	645	695	720
Overall dimension			
L1 Overall length(with fork) (mm)	4704	4754	4800
W1 Overall width(mm)	2000	2000	2000
h2 Mast lowered height (mm)	2500	2500	2625
h4 Overhead guard height (mm)	2480	2480	2480
R1 Min. turning radius (mm)	3370	3415	3450
Min. intersecting aisle (mm)	5400	5610	5675
Speed(load/unload)			
Max. traveling speed (km/h)	24/25	24/25	24/25
Max. lifting speed (mm/s)	350/450	330/450	310/450
Max. gradient (%)	20	20	20
Self weight (kg)	8600	9100	9550
S/P Tread(front/rear) (mm)	1470/1700	1470/1700	1470/1700
L2 Axle distance (mm)	2250	2250	2250
Min.ground clearance			
m2 Mast (mm)	201	201	201
m1 Frame (mm)	248	248	248
STD Engine	Chaochai CY6102BG	Chaochai CY6102BG	Chaochai CY6102BG
Rated power	81kW	81kW	81kW



LG50DT/LG60DT/LG70DT Internal Combustion Forklift

Engine:Chaochai/imported Isuzu/Perkins
Advanced Ergonomical Design
Large Capacity Radiator
Wide View Mast



- Rated Capacity (kg):
- Power Type:

LG50DT	LG60DT	LG70DT
5000	6000	7000
Diesel	Diesel	Diesel



LONKING 龙工
Efficiency Rules the Future